

We want to grow with you



SMARTLIFT



SmartLift



- The lifthead you can rotate in any direction and telescope forward 600 mm.
- Similarly, the flexible head is electrical tiltable up and down, also the head you can rotate manual 360° and 180° sideways. The complete device you can move 100 mm electrical sideways, for a precise and damage-free installation.
- The 2-circuit Vacuumssystem according EN 13155 is battery powered.
- The TGT SmartLift 380 is equipped with a strong electric wheel drive.



- easy control by rear axle

- the 2 - circuit Vacuumsystem according to EN 13155



- powerful front drive with robust wheels for fieldwork

Total weight:	620 kg	Load current:	230 Volt
Overall height:	1390 mm	Integr. charger:	Cetek XT 14000
Overall width:	800 mm	Charging time:	ca. 8 hours
Overall length:	1650 mm	Batteries:	(2x12V)/2x105 A
Telescope length:	600 mm	Operating time:	ca. 30 hours
Mobility of the		wheel drive:	1000W-AC
Flexible suction head:	-100°+100°	Braking system:	electric
Speed-regulation:	infinitely	Suction cups:	4 Stck. ,300mm Dia.
Lateral displacement:	100 mm	2-circuit system:	2 Vacuum pumps
Lifting height:	2400 mm	Payload telescope in/out:	380kg/200kg

Machines for machining of ALU, Fe and PVC profiles

ALUMA ČS s. r. o. • ul. A. Dubčeka 291 • SK - 013 03 Krasňany, okr. Žilina • tel.: +421-0/41-569 26 79 • fax: +421-0/41-569 26 78
 E-mail: alumacs@alumacs.eu • Internet: www.alumacs.sk